




Firma: G Store & Repair doo
Adresa: Bul.Mihajla Pupina 10z/3
Telefon: 011 785 66 66
Fax:
PIB: 112029009
E-mail: office@gstore.rs

Supermicro MBD-X10DRW-N-O, Dual SKT, Intel C612 chipset, 16 DIMM slots, 10 x SATA3, 2 x NVMe, 2 x 1GbE, IPMI, 1 x PCI-E3.0 x32 slot,WIO - R

Šifra: 83868

Kategorija proizvoda: Dodatna oprema za server

Proizvođač: SUPERMIKRO



Cena: 57.168 rsd.

| | |
|--|---|
| Chipset: | Intel C612 |
| CPU Socket Standard: | Socket 2011-3 Intel Xeon E5-2600v3 Series |
| Supports Central Processor Unit: | Intel Xeon E5-2600v4 Series |
| Max. CPU Bus Clock Rate: | 9.6 GTsec |
| CPU Maximum Quantity Supports: | 2 |
| Memory Type: | DDR4 SDRAM |
| Provides Error Checking Method: | ECC 1600MHz(PC3-12800) 2133MHz(PC3-17000) 1866MHz(PC3-14900) |
| Memory Speed: | 2400MHz(PC4-19200) |
| Memory Form Factor: | DIMM 288-pin |
| Maximum Installable System Memory Storage Capacity: | 2 TB |
| Memory Slot Total Quantity: | 16 |
| Memory Features: | Registered Load Reduced RAID |
| Storage Controller Type: | SATA III |
| SATA Controller Interface Type: | Serial ATA III600 |
| RAID Controller Interface Type: | SATA III Level 0 Level 1 Level 10 |
| Supports RAID Level: | Level 5 |
| Video Controller Integrated: | yes |
| Video Chipset: | Aspeed AST2400 |
| LAN Integrated: | yes |
| LAN Chipset: | Intel i350-AM2 Gigabit EthernetFast |
| Data Link Protocol Supports: | EthernetEthernet |
| PCI Express 3.0 x4 Slot Quantity: | 2 |
| SATA III: | 10 |
| LAN: | 2 (RJ-45) |
| Management Port: | 1 (RJ-45) |
| USB2.0: | 4 (4-pin USB (type A)) |
| VGA: | 1 (15-pin DB) |
| USB3.0: | 2 (USB 3.0 (type A)) |
| BIOS Type: | ACPI 1.0 Support AMI ACPI 2.0 Support PCI 2.3 PnP Support USB Keyboard support ACPI 3.0 Support ACPI 4.0 Support SMBIOS 2.7.1 Support UEFI 2.3.1 |
| BIOS Features: | 128Mb SPI Flash EEPROM |