

MB s1700 ASRock Z790 PRO RS

Šifra: 99840

Kategorija proizvoda: Matične ploče

Proizvođač: ASRock

Cena: **25.010,00** rsd.



Tip procesora:	Intel
Podnožje:	Intel® 1700
Čipset:	Intel® Z790
Format ploče:	ATX
Podržana memorija:	DDR5
Bluetooth:	Ne
Podržani procesori:	Podržava 14-tu, 13-tu & 12-tu Gen Intel Core Procesora (LGA1700) Podržava Intel Hybrid Technology Podržava Intel Turbo Boost Max 3.0 Technology Podržava Intel Thermal Velocity Boost (TVB) Podržava Intel Adaptive Boost Technology (ABT)
Memorija:	Dual Channel DDR5 Memory Technology 4 x DDR5 DIMM Slota Podržava DDR5 non-ECC, unbuffered memorija do 7200+(OC)* Max. kapacitet sistemske memorije: 192GB Podržava Intel Extreme Memory Profile (XMP) 3.0
Slotovi za proširenje:	CPU: 1 x PCIe 5.0 x16 Slot (PCIe2), podržava x16 mod Chipset: 1 x PCIe 4.0 x16 Slot (PCIe3), podržava x4 mod 2 x PCIe 3.0 x1 Slot (PCIe1 i PCIe4) 1 x M.2 Socket (Key E), podržava type 2230 WiFi/BT PCIe WiFi module i Intel CNVio/CNVio2 (Integrisan WiFi/BT) Podržava AMD CrossFire
Skladište:	CPU: 1 x Hyper M.2 Socket (M2_1, Key M), podržava type 2260/2280 PCIe Gen4x4 (64 Gb/s) mod Chipset: 1 x Hyper M.2 Socket (M2_2, Key M), podržava type 2260/2280 PCIe Gen4x4 (64 Gb/s) mod 1 x Hyper M.2 Socket (M2_3, Key M), podržava type 2260/2280 PCIe Gen4x4 (64 Gb/s) mod 1 x Hyper M.2 Socket (M2_4, Key M), podržava type 2260/2280 PCIe Gen4x4 (64 Gb/s) mod 8 x SATA3 6.0 Gb/s konektora Podržava RAID 0, RAID 1, RAID 5 i RAID 10 za SATA uređaje za skladištenje Podržava RAID 0, RAID 1 i RAID 5 za M.2 NVMe uređaje za skladištenje
Mrežna karta:	2.5 Gigabit LAN 10/100/1000/2500 Mb/s
Zvučna karta:	7.1 CH HD Audio Realtek ALC897 Audio Codec Nahimic Audio
USB:	1 x USB-C 3.2 Gen 2x2 (Napred) 1 x USB-C 3.2 Gen 2 (Nazad) 1 x USB-A 3.2 Gen 2 (Nazad) 6 x USB 3.2 Gen 1 (2 Nazad, 4 Napred) 8 x USB 2.0 (4 Nazad, 4 Napred)
Konektori na zadnjoj strani:	2 x sloti za antene 1 x PS/2 kombo port za miš/tastaturu 1 x HDMI 1 x DisplayPort 1.4 1 x USB-A 3.2 Gen 2 (10 Gb/s) 1 x USB-C 3.2 Gen 2 (10 Gb/s) 2 x USB-A 3.2 Gen 1 4 x USB-A 2.0 1 x RJ-45 3 x Audio porta

Interni konektori:	1 x eDP Signal konektor 1 x SPI TPM Header 1 x Power LED i Speaker Header 1 x RGB LED Header 3 x Addressable LED Headers 1 x CPU Fan konektor (4-pin) 1 x CPU/Water Pump Fan konektor (4-pin) (Smart Fan Speed Control) 5 x Chassis/Water Pump Fan konektora (4-pin) (Smart Fan Speed Control) 1 x 24 pin ATX Power konektor 2 x 8 pin 12V Power konektora (Hi-Density Power konektor) 1 x Front Panel Audio konektor 1 x Thunderbolt AIC konektor (5-pin) (Podrška ASRock Thunderbolt 4 AIC kartice) 2 x USB 2.0 Headera (Podrška 4 USB 2.0 porta) 2 x USB 3.2 Gen1 Headera (Podrška 4 USB 3.2 Gen1 porta) 1 x USB-C 3.2 Gen2x2 Header na prednjem panelu (20 Gb/s)
--------------------	--